


## ADSS-96B1.3-PE-80M CABLE



**Cable Section Sketch Map**

1	Center Strength Member	FRP+PE		
2	Fiber Unit	Loose Tube	PBT	
		Fiber	96 Single Mode Fibers	G652D
		Fiber Quantity	12 Pcs Fiber× 8 Loose Tubes	
		Fiber Color	Blue、 Orange、 Green、 Brown、 Gray、 White 、 Red、 Black、 Yellow、 Purple、 Pink、 Aqua	
		Loose Tube Color	Blue、 Orange、 Green、 Brown、 Gray、 White 、 Red、 Black	
		Filling (Fiber Jelly)	Thixotropic Jelly	
3	Water Blocking	Water Blocking Yarn		
4	Water Blocking	Water Blocking Tape		
5	Strength Member	Aramid Yarns		
6	Ripcord	2Pcs		
7	Outer Sheath	HDPE	12.8+/-0.5	

### Technical Data Sheet

Item		Unit	Parameter
Cable Standard Weight		kg/km	127
Rated Tensile Strength(RTS)		N	4700
Maximum Allowable Tension(MAT)		N	1800
Every Day Strength(EDS)		N	1200
Min-Bending Radius	Short-Term	mm	20D
	Long-Term	mm	10D
Crush Performance	Short-Term	N/100mm	1000
	Long-Term	N/100mm	300
Suiting Line Voltage Class		Not more than 35kV	
Span		m	80
Suitable Meteorological Condition		Max wind speed: 25m/s, No icing	
Operation	When working or in store	°C	-40°C-+70°C
Temperature	When laying	°C	-10°C-+50°C
Fiber Attenuation Coefficient in Cable		dB/km(1310nm)	≤0.36dB/km
		dB/km(1550nm)	≤0.22dB/km