

# Optical Laser Source

T OP300 S3S4S5 1310/1490/1550nm

## Features

1. 1~3 wavelengths output from one port
2. High stabilization, build in optic isolator
3. Auto Wave ID output
4. Energy save model



## SPECIFICATIONS

Model	M8	M3	S3	S4	S5	S6
Central Wavelength(nm)	850	1300	1310	1490	1550	1625
Stabilization*	±0.05dB / 1 hour;±0.1dB / 8 hours					
Output Power	> - 6dBm @ 1310nm/1490nm/1550nm/1625nm / > -10 dBm @ 850nm/1300nm					
Modulation	270Hz, 1KHz, 2KHz					
Connector	FC/PC (or customize)					
Auto Power Off	No operation in 10 minutes (can be canceled), Low battery energy					
Battery Charge	Yes					
Power Supply	AA * 2 batteries or AC/DC power supply adapter					
Size(H*W*D)	160mm * 75mm * 32mm					
Weight	About 180g					
Storage Temperature	-20 -- +60 °C, < 90%RH					
Operating Temperature	-10 -- +50 °C, < 90%RH					

n

## Accessories

Standard	Optional
Carrying bag*1	User's manual*1
User's manual*1	
User's manual*1	

\* After 5 minutes warm-up, 20±3°C, CW, FC connector

T OP300 S3S4S5      1310/1490/1550nm